



Bar Sliders

Instructions

Congratulations on purchasing the world's finest Bar Sliders. Remove your old bar ends and re-install the Bar Sliders. Do this by removing the originals, loosening the screw only enough to allow you to remove the bar end as an assembly. Remove the metal spacer, rubber spacer, and 6mm nut, and reinstall in the exact order as the originals,(using the 6x50mm allen bolts supplied). Pre-tighten snugly prior to inserting the new bar sliders. Tighten, using a 5mm allen wrench.

Part No. BS-13

Phone: 760-598-2105
Web: <http://www.IntuRace.com>



Bar Sliders

Instructions

Congratulations on purchasing the world's finest Bar Sliders. Remove your old bar ends and re-install the Bar Sliders. Do this by removing the originals, loosening the screw only enough to allow you to remove the bar end as an assembly. Remove the metal spacer, rubber spacer, and 6mm nut, and reinstall in the exact order as the originals,(using the 6x50mm allen bolts supplied). Pre-tighten snugly prior to inserting the new bar sliders. Tighten, using a 5mm allen wrench.

Part No. BS-13

Phone: 760-598-2105
Web: <http://www.IntuRace.com>



Bar Sliders

Instructions

Congratulations on purchasing the world's finest Bar Sliders. Remove your old bar ends and re-install the Bar Sliders. Do this by removing the originals, loosening the screw only enough to allow you to remove the bar end as an assembly. Remove the metal spacer, rubber spacer, and 6mm nut, and reinstall in the exact order as the originals,(using the 6x50mm allen bolts supplied). Pre-tighten snugly prior to inserting the new bar sliders. Tighten, using a 5mm allen wrench.

Part No. BS-13

Phone: 760-598-2105
Web: <http://www.IntuRace.com>



Bar Sliders

Instructions

Congratulations on purchasing the world's finest Bar Sliders. Remove your old bar ends and re-install the Bar Sliders. Do this by removing the originals, loosening the screw only enough to allow you to remove the bar end as an assembly. Remove the metal spacer, rubber spacer, and 6mm nut, and reinstall in the exact order as the originals,(using the 6x50mm allen bolts supplied). Pre-tighten snugly prior to inserting the new bar sliders. Tighten, using a 5mm allen wrench.

Part No. BS-13

Phone: 760-598-2105
Web: <http://www.IntuRace.com>