



Swingarm Sliders

Instructions

Congratulations on purchasing the world's finest swingarm sliders. These sliders are designed to fit on your swingarm where a steel button is sometimes used. Remove the right button (if so equipped) and reinstall using supplied bolt, washer and slider, then remove the left side button (if so equipped) and reinstall using supplied bolt, washer and slider. Use of thread lock compound is recommended.

NOTE: This product is shipped ready to install. If the parts are loose please make sure that the washer is used (between the bushing and button head) under the bolt head.

Part No. SS-9

Phone: (760-598-2105)
Web: <http://www.IntuRace.com>



Swingarm Sliders

Instructions

Congratulations on purchasing the world's finest swingarm sliders. These sliders are designed to fit on your swingarm where a steel button is sometimes used. Remove the right button (if so equipped) and reinstall using supplied bolt, washer and slider, then remove the left side button (if so equipped) and reinstall using supplied bolt, washer and slider. Use of thread lock compound is recommended.

NOTE: This product is shipped ready to install. If the parts are loose please make sure that the washer is used (between the bushing and button head) under the bolt head.

Part No. SS-9

Phone: (760-598-2105)
Web: <http://www.IntuRace.com>



Swingarm Sliders

Instructions

Congratulations on purchasing the world's finest swingarm sliders. These sliders are designed to fit on your swingarm where a steel button is sometimes used. Remove the right button (if so equipped) and reinstall using supplied bolt, washer and slider, then remove the left side button (if so equipped) and reinstall using supplied bolt, washer and slider. Use of thread lock compound is recommended.

NOTE: This product is shipped ready to install. If the parts are loose please make sure that the washer is used (between the bushing and button head) under the bolt head.

Part No. SS-9

Phone: (760-598-2105)
Web: <http://www.IntuRace.com>



Swingarm Sliders

Instructions

Congratulations on purchasing the world's finest swingarm sliders. These sliders are designed to fit on your swingarm where a steel button is sometimes used. Remove the right button (if so equipped) and reinstall using supplied bolt, washer and slider, then remove the left side button (if so equipped) and reinstall using supplied bolt, washer and slider. Use of thread lock compound is recommended.

NOTE: This product is shipped ready to install. If the parts are loose please make sure that the washer is used (between the bushing and button head) under the bolt head.

Part No. SS-9

Phone: (760-598-2105)
Web: <http://www.IntuRace.com>